


NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. GLASS THICKNESS: 6 mm NOMINAL.
3. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

| CONNECTION CHART |             |                  |              |
|------------------|-------------|------------------|--------------|
| PIN              | SIGNAL      | INSULATION COLOR | JACKET COLOR |
| 1                | GROUND      | OVERALL SHIELD   |              |
| 2                | KEY         |                  |              |
| 3                | Y RECEIVE+  | BLU              | BLK          |
| 4                | Y TRANSMIT+ | BLU              | GRY          |
| 5                | Y RECEIVE-  | BLK              | BLK          |
| 6                | Y TRANSMIT- | YEL              | GRY          |
| 7                | GROUND      | INNER SHIELD     |              |
| 8                | X TRANSMIT- | RED              | RED          |
| 9                | X RECEIVE-  | RED              | BLK          |
| 10               | X TRANSMIT+ | GRN              | RED          |
| 11               | X RECEIVE+  | WHT              | BLK          |
| 12               | KEY         |                  |              |



|   |                |              |
|---|----------------|--------------|
| 宇鴻光電股份有限公司<br>ATouch Technologies Co., Ltd. |                |              |
| P/N:  |                | SAW26PT1G1   |
| DRAWN BY                                    | DIMENSION UNIT | ISSUE DATE   |
| JOHNSON TZENG                               | mm             | 05 / 29 / 08 |
| CHECKED BY                                  | SCALE          | REV          |
|   | NOT TO SCALE   | F            |